tion of 131I and without urination during first 2 hours, give the counting-rate variations of 5 to 30% within this period. The whole body counts should be the same while the RI dose in the body is same, inspite of the RI distribution in the body. From the fact that the counting rates of the scattered region measured by the differential setting are fairly constant, even if the RI distribution in the body varies, it is suggested that there would be the best method of counting among the differential and integral count-Five different energy bands of ¹³¹I gamma-ray spectrum were chosen for the measurements of patients and phantoms. They are (1) photopeak: 314-414 keV, (2) scattered region: 200-300 keV, (3) scattered region: 120-220 keV, (4) scattered region: 30-130 keV, and (5) integral over 3 0keV. In this experiment, the variation of RI distribution in the patient's body is replaced by the thickness variation of the water phantom with ¹³¹I or the depth variation of the ¹³¹I point

source in the water phantom. The counting rate vs thickness of the water phantom with 131I is checked with five counting methods. The curve of the photo-peak measurement is exponential and the differences of the counting rates were the largest, while the scattered-region countings (except for 30-130 keV) and the integral counting gave the smallest differences of counting rates for the thickness variations of the water phantom. geometric means of two-directional countings of the 131I point source in the various depth of water give more constant counts than the arithmetic means in the photo-peak measurement. In case of the scatered-region countings and the integral counting, the arithmetic means are better than the geometric means. The counting methods of scattered region of 120-220 keV and integral are superior to the other three. same results were obtained with the patients' countings.

Experiments on the Medium Level Whole Body Counter

Н. КАКЕНІ

Department of Radiology, Chiba University Hospital, Chiba

- 1. The medium level whole body counter, manufactured at the ORINS medical Division, Oak Ridge, Tenn. has four detectors, which consist of four $3'' \times 3''$ NaI crystals in a trough-like container of $1\,1/4''$ thickness. This machine is suitable for the measurement of the radioisotope range of $0.1 \sim 100 \rm MC$ in a patient's body, namely is used for the medium level range of sensitivity between high and low level counters.
 - 2) When the ¹³¹I capsule is given to a
- patient, at first it shows a point source in the stomach. If the capsule is solved, ¹³¹I will be absorbed by the gastrointestinal tract and it will circulates in the blood through the body. Then it is taken up gradually by the thyroid gland.
- 3. The counting was made both at the peak region of ¹³¹I and at the scatlered region, and the data were compared each other. Better results were obtained when ¹³¹I was measured at the scattered region.

On the Conception of Medical Universal Human Counter

H. HIRAMATSU and K. HISADA

Department of Radiology, School of Medicine, Kanazawa University, Kanazawa

Since a radio-pharmaceutical is administered to a patient in clinical tracer studies except for a measurement of natural ⁴⁰K, as for a medical human counter its clinical usefulness is more preferable to its sensitivity.

No one wants to be confined in a steel